



with valveblock sideshift dependent on the opening range - 2 hydraulic functions

## Technical Data

Model	Cap. kg	LCD mm	A mm	B mm	D mm	E mm	G mm	VSmax mm	V mm	CofG Z mm	CofG <sub>v</sub> Y mm	Weight kg	Price 人民币	Add-on price per 100mm fork length 人民币
1,5T160BIZ	1.600	500	170-870	1.040	40	100	1.200	±175	91	261	197	210	On request	On request
1,5T160BIZ	1.600	500	170-970	1.150	40	100	1.200	±200	91	255	200	216	On request	On request
2T160BIZ	2.500	500	130-830	1.040	45	120	1.200	±175	91	300	184	245	On request	On request
2T160BIZ	2.500	500	130-930	1.150	45	120	1.200	±200	91	293	187	251	On request	On request
2,5T160BIZ	2.500	600	130-830	1.040	50	120	1.200	±175	101	305	186	267	On request	On request
2,5T160BIZ	2.500	600	130-930	1.150	50	120	1.200	±200	101	300	188	273	On request	On request
3,5T160BIZ	3.600	500	130-930	1.150	50	150	1.200	±200	111	292	221	355	On request	On request
3,5T160BIZ	3.600	500	130-1.130	1.350	50	150	1.200	±250	111	283	225	370	On request	On request
4,5T160BIZ	5.000	500	130-1.130	1.350	60	150	1.200	±250	114	263	240	469	On request	On request
4,5T160BIZ	5.000	500	130-1.310	1.550	60	150	1.200	±295	114	255	243	489	On request	On request
4,8T160BIZ <sup>1)</sup>	5.000	600	130-1.130	1.350	70	150	1.200	±250	114	291	232	512	On request	On request
4,8T160BIZ <sup>1)</sup>	5.000	600	130-1.310	1.550	70	150	1.200	±295	114	283	236	532	On request	On request
6T160BIZ	6.000	600	200-1.200	1.460	70	150	1.200	±250	141	264	336	642	On request	On request
6T160BIZ	6.000	600	200-1.400	1.650	70	150	1.200	±300	141	258	340	663	On request	On request
6T160BIZ	6.000	600	200-1.600	1.860	70	150	1.200	±350	141	239	343	685	On request	On request

Model	Cap. kg	LCD mm	A mm	B mm	D mm	E mm	G mm	VSmax mm	V mm	CofG Z mm	CofG Y mm	Weight kg	Price 人民币	Add-on price per 100mm fork length 人民币
8T160BIZ	8.000	600	200-1.600	1.860	70	150	1.200	±350	141	252	343	685	On request	On request
8T160BIZ	8.000	600	200-1.800	2.060	70	150	1.200	±400	141	233	353	755	On request	On request
8T160BIZ	8.000	600	200-2.000	2.260	70	150	1.200	±450	141	228	354	771	On request	On request
8T160BIZ	8.000	600	210-2.060	2.400	70	150	1.200	±462,5	141	225	357	785	On request	On request
10T160BIZ	8.000	900	100-1.730	2.060	70	200	1.200	±407,5	178	268	350	963	On request	On request
10T160BIZ	8.000	900	100-1.900	2.260	70	200	1.200	±450	178	263	352	991	On request	On request
10T160BIZ	8.000	900	100-2.000	2.400	70	200	1.200	±475	178	258	357	1.015	On request	On request
10T160BIZ	8.000	1.100	100-1.730	2.060	80	200	1.200	±407,5	178	279	346	1.012	On request	On request
10T160BIZ	8.000	1.100	100-1.900	2.260	80	200	1.200	±450	178	274	349	1.040	On request	On request
10T160BIZ	8.000	1.100	100-2.000	2.400	80	200	1.200	±475	178	268	353	1.064	On request	On request
12T160IZ	12.000	600	370-2.000	2.400	80	200	1.200	±407,5	178	225	585	1.450	On request	On request
12T160IZ	12.000	600	300-2.300	2.700	80	200	1.200	±500	178	216	590	1.540	On request	On request
12T160IZ	12.000	600	500-2.700	3.100	80	200	1.200	±550	178	207	600	1.640	On request	On request
16T160IZ	16.000	600	370-2.000	2.400	90	200	1.200	±407,5	178	222	585	1.600	On request	On request
16T160IZ	8.000	1.200	370-2.000	2.400	90	200	2.400	±407,5	178	475	498	1.905	On request	On request
16T160IZ	8.000	1.200	500-2.700	3.100	90	200	2.400	±550	178	438	517	2.090	On request	On request
24T160IZ	24.000	600	270-1.900	2.400	90	250	1.200	±407,5	178	244	568	1.755	On request	On request
24T160IZ	12.000	1.200	270-1.900	2.400	90	250	2.400	±407,5	178	521	474	2.137	On request	On request
24T160IZ	12.000	1.200	400-2.600	3.100	90	250	2.400	±550	178	486	492	2.320	On request	On request
32T160IZ	32.000	600	270-2.100	2.600	100	250	1.200	±457,5	178	230	585	2.020	On request	On request
32T160IZ	16.000	1.200	270-2.100	2.600	100	250	2.400	±457,5	178	493	493	2.435	On request	On request
32T160IZ	16.000	1.200	260-2.600	3.100	100	250	2.400	±585	178	470	505	2.570	On request	On request

1) 4,8T with capacity (kg/mm) 2.700/1.200 available upon request.

CofG and weight measurements do not take the cheek plates into account.

Fork carriage drawings, roller studs and chain anchors to be supplied by customer if necessary.

Not suitable for clamping between the forks.

Available without sideshift.

Load backrest see model T479 and T479.1

Larger models and different widths available upon request.

with screw-on forks available upon request: IZA-Version



---

### Specification:

The integrated KAUP Fork Positioner

T160IZ(A) is an economical integrated Fork Positioner with welded on or screwed on forks offering an excellent view to the fork tips and load.

Compared to hook-on attachments in the T160Z(A) range this Fork Positioner has an even better, higher residual capacity.

---

### Qualities:

- For moderately heavy operation
- Excellent residual capacity
- High stability with optimal tare weight
- Very good visibility conditions
- Valve block sideshift serially
- Supplied with welded forks
- Supplied optionally with screw on forks for wear intensive operation (A-version)