



with independent sideshift - 2 hydraulic functions

## Technical Data

Model	Cap. kg	LCD mm	S mm	A mm	B mm	C mm	H mm	I mm	K mm	ISO	Md $\Delta$ -P = 125 bar Nm	Req. oil volume per rotation ltr.	V mm	CofG Z mm	Weight kg	Price 人民币
<b>1T391.2S</b>	1.800	500	±100	780	890	858	213	294	32	2	6.013	7,6	192	99	198	On request
<b>2T391.1S</b>	2.500	500	±100	790	1.040	858	269	492	32	2	7.700	9,7	172	90	255	On request
<b>2,5T391.1S</b>	3.200	500	±100	790	1.100	850	269	492	40	3	7.700	9,7	197	108	318	On request
<b>1T391.2.3S</b>	1.800	500	±100	780	890	858	213	294	32	2	6.013	7,6	192	99	198	On request
<b>2T391.1.3S</b>	2.500	500	±100	790	1.040	858	269	492	32	2	7.700	9,7	172	90	255	On request
<b>2,5T391.1.3S</b>	3.200	500	±100	790	1.100	850	269	492	40	3	7.700	9,7	197	108	318	On request

Rotators with higher rotating speeds available upon request

Other fork carriage widths available upon request.

Add-on price for lateral supporting fork 1.000 mm.

Lateral supporting fork 1.000 mm (add-on-price)

Downhold T167 to empty metal grid boxes etc on request

Matching forks for KAUP-Rotators on request.

When forks are used in combination with a Rotator extremely high strain is applied to the lower fork angle when rotating a load which in turn strains the lower brackets.

For this type of operation KAUP recommends forks with strengthened lower brackets. Strengthened lower brackets can be ordered for all ISO forks model T180.



## Rotator 360° endless, fishing industry T391S - T391.3S

---

---

### Specification:

Beside the foundry implementation the

KAUP Rotator 360° endless T391 is also available in two fishing

implementations. These attachments are adapted to the demands of this

operational area with special sea-water resistant paint, galvanised

screws, flanges and fork carriages (according to implementation) as well

as drill holes sealed with silicon.

---

### Qualities:

- Good visibility conditions
- Good residual capacity
- Rotation 360° endlessly
- Robust construction with gear drive
- Independent sideshift serially
- Original forks usable
- Lateral supporting fork and load stabilizers optionally