



with independent sideshift, 2 hydraulic functions - without forks - for forks acc. to ISO 2330

Technical Data

Model	Cap. kg	LCD mm	S mm	A mm	B mm	C mm	ISO	V mm	CofG Z mm	Weight kg	Price 人民币
1T410Z	1.500	500	±100	540-1.500	750	240	2	183	88	173	On request
1T410Z	1.500	500	±100	540-1.720	970	240	2	183	87	196	On request
1T410Z	1.500	500	±100	550-1.900	1.130	240	2	183	87	206	On request
1T410Z	1.500	500	±100	530-1.930	1.200	240	2	183	86	211	On request

1,6T410Z	2.300	500	±100	530-1.710	1.040	240	2	188	86	231	On request
1,6T410Z	2.300	500	±100	560-1.860	1.130	240	2	188	85	237	On request
1,6T410Z	2.300	500	±100	560-2.060	1.330	240	2	188	85	250	On request

1,6T400Z	2.300	500	ohne	540-1540	850	240	2	181	81	212	On request
----------	-------	-----	------	----------	-----	-----	---	-----	----	-----	------------

2,5T410Z	2.800	500	±100	530-1.710	1.040	240	2	198	91	245	On request
2,5T410Z	2.800	500	±100	560-1.860	1.130	240	2	198	90	251	On request
2,5T410Z	2.800	500	±100	560-2.060	1.330	240	2	198	89	264	On request

2,5T400Z	2.800	500	ohne	540-1540	850	240	2	191	86	225	On request
----------	-------	-----	------	----------	-----	-----	---	-----	----	-----	------------

2,5T410Z	3.000	500	±100	560-1.860	1.130	240	3	208	84	281	On request
2,5T410Z	3.000	500	±100	560-2.060	1.330	240	3	208	84	295	On request

3T410Z	3.600	500	±100	560-1.860	1.130	240	2	223	95	374	On request
3T410Z	3.600	500	±100	560-2.060	1.330	240	2	223	94	392	On request
3T410Z	3.600	500	±100	550-2.170	1.460	240	2	223	94	403	On request
3T410Z	3.600	500	±100	560-1.860	1.130	240	3	223	95	374	On request
3T410Z	3.600	500	±100	560-2.060	1.330	240	3	223	94	392	On request
3T410Z	3.600	500	±100	550-2.170	1.460	240	3	223	94	403	On request

4T410Z	4.150	500	±100	560-1.860	1.130	240	3	233	100	420	On request
--------	-------	-----	------	-----------	-------	-----	---	-----	-----	-----	------------

Model	Cap. kg	LCD mm	S mm	A mm	B mm	C mm	ISO	V mm	CofG Z mm	Weight kg	Price 人民币
4T410Z	4.150	500	±100	560-2.060	1.330	240	3	233	99	440	On request
4T410Z	4.150	500	±100	550-2.170	1.460	240	3	233	99	452	On request

4,5T410Z	5.000	500	±100	580-1.930	1.200	240	3	258	114	483	On request
4,5T410Z	5.000	500	±100	540-1.980	1.330	240	3	258	113	499	On request
4,5T410Z	5.000	500	±100	570-2.170	1.460	240	3	258	112	515	On request
4,5T410Z	5.000	500	±100	580-2.280	1.550	240	3	258	112	526	On request

4,8T410Z	5.000	600	±100	580-1.930	1.200	240	3	253	113	487	On request
4,8T410Z	5.000	600	±100	540-1.980	1.330	240	3	253	112	501	On request
4,8T410Z	5.000	600	±100	570-2.170	1.460	240	3	253	111	517	On request
4,8T410Z	5.000	600	±100	580-2.280	1.550	240	3	253	111	527	On request

5T410Z	6.200	600	±160	530-2.160	1.550	260	4	260	99	610	On request
5T410Z	6.200	600	±160	800-2.700 ¹⁾	1.550	260	4	260	102	670	On request
5T410Z	6.200	600	±160	530-2.430	1.820	260	4	260	99	643	On request

1) Transport of europallets lengthwise not possible.

Not suitable for clamping between the forks.

Forks see model T180.

Also available without sideshift, model T400Z

Fork Positioner with cylinder- and sideshift protection upon request.

Load Backrest see model T179.



Specification:

The robust KAUP Fork Positioner T410Z is the alternative to Fork Positioner T466B when a large opening range is required on a small construction width. This attachment is ideal for heavy duty operation and is supplied without forks. Numerous individual configurations are possible.

Qualities:

- Strengthened design
- Good residual capacity
- Independent sideshift serially
- Original forks or Telescopic Forks can be used