



with valveblock sideshift dependent on the opening range - 2 hydraulic functions

Technical Data

Model	Cap. kg	LCD mm	A mm	B mm	D mm	E mm	G mm	VSmax mm	ISO	V mm	CofG Z mm	CofG _v Y mm	Weight kg	Price 人民币	Add-on price per 100mm fork length 人民币
4T411BZ	4.500	500	330-2.530	2.030	60	120	1.200	±550	3	168	184	264	805	On request	On request
4,8T411BZ	6.000	500	220-1.850	1.550	60	150	1.200	±407,5	3	184	209	275	885	On request	On request
5T411BZ	6.300	600	220-1.850	1.550	60	150	1.200	±407,5	4	184	203	321	925	On request	On request
5T411BZ	6.300	600	180-2.080	1.860	60	150	1.200	±475	4	184	195	325	1.010	On request	On request
5T411BZ	6.300	600	380-2.480 ¹⁾	1.860	60	150	1.200	±525	4	184	195	326	1.014	On request	On request
5T411BZ	6.300	600	310-2.510 ¹⁾	2.030	60	150	1.200	±550	4	184	191	328	1.046	On request	On request
6T411BZ	8.000	600	170-1.800	1.550	60	200	1.200	±407,5	4	194	233	314	1.165	On request	On request
6T411BZ	8.000	600	130-2.030	1.860	60	200	1.200	±475	4	194	226	318	1.225	On request	On request
6T411BZ	8.000	600	330-2.430 ¹⁾	1.860	60	200	1.200	±525	4	194	225	319	1.229	On request	On request
6T411BZ	8.000	600	200-3.800 ¹⁾	3.390	50	300	1.200	±900	4	194	218	315	1.545	On request	On request
8T411BZ	8.000	900	210-1.840 ¹⁾	1.550	70	200	1.200	±407,5	4	230	230	333	1.435	On request	On request
8T411BZ	8.000	900	330-2.530 ¹⁾	2.000	70	200	1.200	±550	4	230	219	339	1.564	On request	On request
8T411BZ	8.000	900	400-2.900 ¹⁾	2.400	70	200	1.200	±625	4	230	211	344	1.672	On request	On request
8T411BZ²⁾	5.000	1.200	2.600-5.600 ¹⁾	4.500	70	200	1.200	±750	4	230	135	380	2.515	On request	On request

1) Transport of europallets lengthwise not possible.

2) Alternatively available with third fork in the centre. (add-on-price)

Not suitable for clamping between the forks.

With screw-on forks available upon request T411BZA

Load Backrest see model T179.

Also available without sideshift, model T401BZ



Specification:

The KAUP hook-on Fork Positioner T411BZ

is a robust attachment with large opening ranges for exceptionally heavy duty operation - ideal for uneven surfaces. The construction of this Fork Positioner predestines it for handling long loads and steel girders and especially for heavy duty operation in, for example, concrete plants.

Qualities:

- Very large opening ranges
- Good residual capacity
- Valve block sideshift - dependent on opening range - serially
- Opening range significantly larger than the construction width
- Independent sideshift optionally
- Screw-on forks optional