



with independent sideshift - with mechanical equilibration plates with Vulcollan coating - 2 hydraulic functions

Technical Data

| Model | Cap. kg | LCD mm | S mm | A mm | B mm | G mm | ISO | V mm | CofG Z mm | CofG _v Y mm | Weight kg | Price 人民币 |
|----------|------------|-----------|---------|-----------|---------|---------|-----|---------|-----------------|------------------------------|--------------|--------------|
| 2T412V-3 | 2.000 | 500 | ±100 | 275-1.575 | 1.130 | 1.260 | 2 | 143 | 365 | 160 | 560 | On request |
| 2T412V-3 | 2.000 | 500 | ±100 | 275-1.575 | 1.130 | 1.260 | 3 | 143 | 365 | 160 | 560 | On request |

| | | | | | | | | | | | | |
|----------|-------|-----|------|-----------|-------|-------|---|-----|-----|-----|-----|------------|
| 3T412V-3 | 2.500 | 500 | ±100 | 295-1.595 | 1.130 | 1.260 | 3 | 152 | 338 | 176 | 630 | On request |
|----------|-------|-----|------|-----------|-------|-------|---|-----|-----|-----|-----|------------|

Available with cylinder- and sideshift protection upon request
Also available without sideshift, model T402V-3
Variations in arm dimensions upon request.
Load Backrest see model T179.



Specification:

KAUP Block Clamps T412V-3 are fitted with clamping arms with especially large mechanical equilibration plates with Vulcollan coating. This attachment is particularly suited for handling large blocks or packets of blocks with plane surfaces and high dimensional stability.

Qualities:

- Mechanical equalisation
- Low lost load centre - excellent residual capacity
- Very good visibility conditions
- Independent sideshift serially
- Load Backrest optionally